


TECHNICAL SPECIFICATION

SEAEYE PANTHER XT PLUS LIGHT WORK CLASS ROV SYSTEM



ROVOP

KNOWLEDGE IN DEPTH

SEAEYE PANTHER XT PLUS LIGHT WORK CLASS ROV SYSTEM

MODEL

Seaeye Panther XT Plus

MANUFACTURER

Saab Seaeye Ltd.

CLASSIFICATION

DNV Safe Area Only

TYPE

Light Work Class System
Free Swimming
Crane-based LARS

STRUCTURE

Polypropylene Chassis

FRAME & FITTINGS

Stainless steel lifting frame
Stainless steel fittings and fasteners

ROV SPECIFICATIONS

ROV Depth rating	1,000msw
Length	2,140mm
Width	1,060mm
Height	1,217mm
Payload	150kg
Launch weight	800kg
Thrust Forward	353 kgf
Thrust Lateral	248 kgf
Thrust Vertical	105 kgf
Forward Speed	>4knots

UMBILICAL DATA CHANNELS

RS232	4
RS485	2
10/100 Ethernet	1

VIDEO CHANNELS

SD PAL/NTSC	4
-------------	---

WORK CAPABILITIES

Drill support
Construction support
Cable and pipeline pre- and post-lay
Survey
Platform inspection and cleaning
Salvage and oceanographic
Survey jacket inspection and cleaning
Dredging
IMR
Special tooling
Pipe lay barge support
Suction anchor installation

SYSTEM POWER REQUIREMENTS

CONTROL VAN INPUT

Input Voltage	3-ph 380-480 VAC
Host power supply	63 A

CABIN 24KVA / 31A

TOOLING 9KW 660vac

LARS

Input Voltage	3-ph 380-480 VAC
Host power supply	63 A